



Grade Specifications:	FR70	FR80	FR100	Fire Retardant -	Bleached White
Specification Item	Light Traffic	Standard Traffic	Heavy Traffic	Meets or Exceeds TAPPI METHOD	Unit of Measure
Basis Weight \pm 3%	77.00 70.00	88.00 80.00	110.00 100.00	N/A	lbs/3300sf lbs/3000sf
Caliper	6.50	7.40	9.20	T411 360	mils
Tear	110.00	125.00	130.00	T414 312	grams force
Tensile	50.00	58.00	58.00	T494 325	lbs force/inch
Porosity	15.00	15.00	20.00	T547 372	seconds
Brightness \pm 2%	87.00	87.00	87.00	T452 390	%
Flame Resistance	4.00	4.00	4.00	T461 cm-00	inches
Roll Length*	500.00 152.40	300.00 91.44	300.00 91.44	N/A	linear feet linear meters

*Roll Width All grades available in 36, 42, 60, 72, 84 in (91.4, 106.7, 152.4, 182.9, 213.4 cm)

FLOOR PAPER INSTALLATION

1. Ensure floor is dust free for best adhesion of tape (industrial strength recommended). Tack cloth is recommended to pick up residual dust.
2. Start in a corner. Tape down the end of the roll.
3. Unroll paper to desired length and cut.
4. Tape down loose end.
5. Repeat process until floor is covered.
6. Tape down seams as desired.

